

RED CEDAR SORT SPECIFICATIONS




Code: 44

L SORT RED CEDAR

- | | | | |
|----|-----------|----|---|
| L1 | 20' - 27' | A. | Min. dia. 20"; Min. L 20'. |
| L2 | 28' - 35' | B. | Smooth appearing #3 and better surface quality. |
| L3 | 36' - 40' | C. | Max. defect 40 % ; Max. L deduction 20 %. |
| | | D. | Slabs with min. of 300bf of #2 & Better are acceptable. |
| | | E. | Buck off excessive L defect and broken ends. |
| | | F. | Must be suitable for producing clears. |

Code: 45

CIRCLE SH RED CEDAR

- | | | | |
|---|-----------|----|---|
|  SH1 | 12' - 27' | A. | Min. dia. 20"; Min. L 12'. |
|  SH2 | 28' - 35' | B. | Buck excessive butt defect. |
|  SH3 | 36' - 40' | C. | Max. defect 30% excluding checks |
| | | D. | Twist shall not exceed 3"/ft. |
| | | E. | Slabs must have a min. of 400bf |
| | | F. | Must be merchantable for producing lumber recovery. |

Code: 46

SH RED CEDAR

- | | | | |
|-----|-----------|----|---|
| SH1 | 12' - 27' | A. | Dia. 8" thru 19"; Min. L 12'. |
| SH2 | 28' - 35' | B. | Buck excessive end defect; No excessive twist. |
| SH3 | 36' - 40' | C. | Slabs must have a min. of 200bf. |
| | | D. | Must be merchantable for producing lumber recovery. |
| | | E. | DOUBLE WRAP all bundles!! Max. 25 ton bundles. |

Code: 41

C SORT RED CEDAR

- | | | | |
|----|-----------|----|----------------------------|
| C1 | 12' - 27' | A. | Min. diam. 20"; Min. L 12' |
| C2 | 28' - 35' | B. | Max defect 66% |
| C3 | 36' - 40' | C. | Scribner Scale only |

Sort Specifications are subject to change without notice.